

**EVO**

## Green Thermal Receipt Printer

The EVO Green Thermal Receipt Printer is one of our most efficient receipt printers. Engineered to operate day-in and day-out in the harshest of environments, the EVO Green provides the steadfast performance you need while using a fraction of the energy. Perfect for high volume retail and hospitality operations, the EVO Green features quick receipt printing, JamFree Autocutter Technology, and is backed by the best warranty in the industry.



### Key Features



**Print Speed**

220mm/sec



**Accessories Included**

Power supply and interface cables included



**Paper Loading**

Drop-in easy thermal paper loading



**AutoCutter**

JamFree AutoCutter technology



**Multiple Interfaces**

USB, Serial, Ethernet



**Emulation**

ESC/POS and OPOS compatible



**Wall-Mountable**

Convenient mounting capabilities



**Energy Star Certified**

Helps cut energy costs

■ **POS-X Warranty**

**Industry-leading Warranty Protection**

- 3 year warranty
- \*2-day Advance Exchange - standard on all products
- Warranty extensions and overnight exchanges are available to provide means to further reduce the total cost of ownership

\*Available in USA and Canada

■ **POS-X Service and Support**

**24/7 Technical Support and Lifetime Customer Support**

- 24/7 access to our USA-based experienced technical support representatives
- Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products

<b>PART NUMBER</b>	EVO-PT3-2GUS	EVO-PT3-2GUSE
<b>INTERFACE SPECIFICATIONS</b>		
Interfaces	USB/Serial	USB/Serial/Ethernet
Interface Details	USB 2.0/RS-232C	USB 2.0/RS-232C/(10/100)
Emulation	ESC/POS Command Compatible OPOS	
Print Method	Direct Thermal	
Printing Speed	7.87"/sec (220 mm/sec)	
Print Resolution	180 DPI x 180 DPI	
Printing Direction	Unidirectional with Friction Feed	
Sensors	Cover Open, Paper Low, Paper End	
Cash Drawer Port	1 Port, 2 Internal Circuits (24 V, 1 A max)	
Reliability	TPH Life 99.42 miles (160Km) MCBF 60,000,000 Lines	
<b>PAPER</b>		<b>PHYSICAL</b>
Type	Thermal Paper	Dimension (WxDxH)
Width	1.9" (50mm) - 3.15" (80mm)	6.1" x 8" x 6.1" (155mm x 203mm x 155mm)
Thickness	0.002" (0.06mm) - 0.0035" (0.09mm)	Weight
Roll Diameter	Max 3.15" (80mm)	3.7 lbs (1.7 kg)
Roll Core Inner Diameter	0.492" (12.5mm) ± 0.019" (0.5mm)	Color
Character Set	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page) International Characters 14	Electrical
Character/Line	Font A (12 x 24) 42 columns Font B (9 x 17) 56 columns	100–240 VAC 50/60 Hz (input) 24 VDC/1.5 A (output)
Barcodes Supported	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, PDF 417(2D)	<b>ENVIRONMENTAL</b>
<b>AUTO CUTTER</b>		Temperature
Type	JamFree auto-retracting guillotine	41°F to 104°F (5°C to 40°C) operating -4°F to 140°F (-20°C to 60°C) storage
Life	1,500,000 Cuts	Humidity
Cutting Method	Full/Partial Cut	35% to 80% non condensing (operation) 10% to 90% non condensing (storage)
		Warranty
		3-year warranty with free *2-day Advance Exchange Service, 2-year on Autocutter and Print Head
		Certifications
		FCC, UL, CE, Energy Star, RoHs, NOM
		Operating System
		WIN 95, WIN 98, WIN 2000, WIN XP, VISTA, Win 7, Win 8, OPOS drivers available
		<b>WARRANTY EXTENSION AND UPGRADES</b>
		ZWE-CRW
		2-Year Warranty Extension
		ZOE-CRW3
		*3-Year Overnight Exchange
		ZOE-CRW5
		*5-Year Overnight Exchange

\*Available in USA and Canada



1975 Midway Lane, Suite O  
 Bellingham, WA 98226  
 sales@pos-x.com  
 360.738.8433  
 www.pos-x.com

